

60EX-4

Eccentric key with a stroke of ± 0.5 mm.



FEATURES

Eccentric key with a stroke of \pm 0.5 mm. Used with:

- Laser Beam Couplers series 60SMS with focal length ≤ 11 mm
- Fiber Collimators series 60FC with focal length ≤
 11 mm
- Compact Laser Line Generators with Ø 12mm (except for semi-telecentric lines)
- Compact Laser Focus Generators with Ø 12mm

Please note: In some cases.e.g. for short wavelengths and end cap fibers the stroke of the eccentric key type 60EX-4 might be too small. Please try using the eccentric key 60EX-5 with a larger stroke instead to adjust the focus position.

products/fiberoptics/fibercoupler/pm/60sms.html

TECHNICAL DATA

60EX-4

Order Code	60EX-4
Stroke	± 0.5 mm
Total length	
Material	Steel
Weight	6 g
RoHS compliant	Yes



RELATED PRODUCTS

ADJUSTMENT TOOLS FIBER OPTICS

ADJUSTMENT TOOLS LASER MODULES

60EX-4-L Alternative eccentric key with long handle with a

stroke of ± 0.5 mm.

60EX-5 Eccentric key with a stroke of \pm 1.0 mm.

60EX-5-L Alternative eccentric key with long handle with a

stroke of ± 1.0 mm.

55EX-5 Eccentric key with a stroke of \pm 1.5 mm.

55EX-5-L Alternative eccentric key with long handle with a

stroke of \pm 1.5 mm.

50HD-15 Hex key WS 1.5

9D-16 Screwdriver WS 1.6

9D-12 Screwdriver WS 1.2

This is a printout of the page https://sukhamburg.com/products/details/60EX-4 from 5/13/2024

CONTACT

For more information please contact:

Schäfter + Kirchhoff GmbH

Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com



LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]