Bulkhead Fiber Adapters

Fiber Adapters without Optics



FEATURES

Bulkhead fiber adapters are used either for beam outputs, where no collimation or focusing of the radiation exiting the fiber is necessary, or for beam coupling into connectorized fibers, when a separate coupling optics such as a microscope optics is used.

- FC, F-SMA and LSA (comp. with DIN, AVIO or AVIM) connector
- Inclined coupling axis for APC (angled polish)
- Axial stop of the fiber ferrule for a constant focus position (FC and LSA only)
- Grub screw for an additional locking of the fiber ferrule (FC and LSA only)
- Different mechanical designs
- TILT alignment as an option
- Mechanics made of Titanium as an option

ORDER OPTIONS

Connector Type <i>l</i> Polish angle	Ø 12 mm	ø 25 mm	System Mount Ø 19.5 mm	Flange Mount w/o Flange	Flange Mount w. Flange Ø 20 mm	Flange Mount w. Flange Ø 25 mm	TILT	Titanium
FC-PC, 0°	<u>12AF-0-</u> <u>FC</u>	<u>25AF-0-</u> <u>FC</u>		<u>10AF-0-</u> <u>FC</u>	10AF-0- FC+PP1020	10AF-0- FC+PP1025	-	-
FC-PC, 0°	<u>12AF-0-</u> <u>FC-Ti</u>			10AC-0- FC-Ti	10AF-0- FC+PP1020-TI		-	Yes
FC-PC, 0°		<u>25AM-0-</u> <u>FC</u>	<u>19.5AC-0-</u> <u>FC</u>				Yes	-
FC-PC, 0°			19.5AC-0- FC-TI				Yes	Yes
FC-APC, 8°	<u>12AF-4-</u> <u>FC</u>	<u>25AF-4-</u> <u>FC</u>		<u>10AF-4-</u> <u>FC</u>	10AF-4- FC+PP1020	10AF-4- FC+PP1025	-	-
FC-APC, 8°	<u>12AF-4-</u> <u>FC-Ti</u>			<u>10AF-4-</u> <u>FC-Ti</u>	<u>10AF-4-</u> <u>FC+PP1020-TI</u>		-	Yes
FC-APC, 8°		<u>25AM-4-</u> <u>FC</u>	19.5AC-4- FC				Yes	-
FC-APC, 8°			19.5AC-4- FC-TI				Yes	Yes
F-SMA, 0°	<u>12AF-0-</u> <u>SMA</u>	25AF-0- SMA		10AF-0- SMA	10AF-0- SMA+PP1020	10AF-0- SMA+PP1025	-	-
F-SMA, 0°		25AM-0- SMA	19.5AC-0- SMA				Yes	-
F-SMA, 5° ¹		<u>25AM-23-</u> <u>SMA</u>	19.5AC-23- SMA				Yes	-
F-SMA, 8° ²		<u>25AM-4-</u> <u>SMA</u>	19.5AC-4- SMA				Yes	-
LSA-PC, 0° ³	12AF-0- LSA	25AF-0- LSA		10AF-0- LSA	10AF-0- LSA+PP1020	10AF-0 - LSA+PP1025	-	-
LSA-PC, 0° ³		25AM-0- LSA	19.5AC-0- LSA				Yes	-
LSA-APC, 8° ⁴	12AF-4- LSA	25AF-0- LSA		<u>10AF-4-</u> <u>LSA</u>	<u>10AF-4-</u> <u>LSA+PP1020</u>	10AF-4- LSA+PP1025	-	-
LSA-APC, 8° ⁴		25AM-4- LSA	19.5AC-4- LSA				Yes	-

¹ Compatible to fiber connectors of type SMA-905 High Power with a 5° polish

² Compatible to fiber connectors of type SMA-905 High Power with a 8° polish

³ Compatible with connectors of type DIN-PC, AVIO-PC and AVIM-PC

⁴ Compatible with connectors of type DIN-APC, AVIO-APC and AVIM-APC

This is a printout of the page

https://sukhamburg.com/products/fiberoptics/fibercable/accessories/bulkheadadapter.html from 5/1/2024

CONTACT

For more information please contact: Schäfter + Kirchhoff GmbH Kieler Str. 212 22525 Hamburg Germany

Tel: +49 40 85 39 97-0 Fax: +49 40 85 39 97-79

info@sukhamburg.de www.sukhamburg.com

LEGAL NOTICE

Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [more]