

## Polarization Filters 5PF

for attaching to 60FC Fiber Collimators



### FEATURES

Polarization filters with system mount Ø 8 mm for attaching to [60FC](#) Fiber Collimators (with outer diameter Ø 12 mm).

These filters transmit only the linear polarized component of the radiation.

There are two series:

- Polarization beam splitter cubes with deflection of the unwanted orthogonally polarized radiation
- Dichroic polarization filter. The filter is laminated to a glass substrate with an 1.5° inclined mounting in order to avoid direct back-reflections
- Free rotation for best adjustment with positional locking using radially arranged screws.
- Polarization extinction ratio 10.000:1
- Surface deviation  $< \lambda/4$
- Wavelength range UV - IR
- Broadband AR Coating
- Optional long-form housing (-L) with system mount Ø 8 mm for adding additional attachment optics

## ORDER OPTIONS

Order Code	Series	Polarizer Type	Spectral Range	Extinction	Transmission	Clear Aperture	System Mount	Front Fitting
<a href="#">5PF-P-600-S</a>	5PF-P	dichroic	600 - 850 nm	$10^4 : 1$	> 84 - 93 %	5 mm	Ø 8 mm	-
<a href="#">5PF-P-750-S</a>	5PF-P	dichroic	750 - 1250 nm	$10^4 : 1$	> 87 - 93 %	5 mm	Ø 8 mm	-
<a href="#">5PF-P-1300-S</a>	5PF-P	dichroic	1280 - 1500 nm	$10^4 : 1$	> 96 - 98 %	5 mm	Ø 8 mm	-
<a href="#">5PF-P-600-L</a>	5PF-P	dichroic	600 - 850 nm	$10^4 : 1$	> 84 - 93 %	5 mm	Ø 8 mm	Ø 8 mm
<a href="#">5PF-P-750-L</a>	5PF-P	dichroic	750 - 1250 nm	$10^4 : 1$	> 87 - 93 %	5 mm	Ø 8 mm	Ø 8 mm
<a href="#">5PF-P-1300-L</a>	5PF-P	dichroic	1280 - 1500 nm	$10^4 : 1$	> 96 - 98 %	5 mm	Ø 8 mm	Ø 8 mm
<a href="#">5PF-C-400-S</a>	5PF-C	cube	390 - 480 nm	$10^4 : 1$	> 95 %	4 mm	Ø 8 mm	-
<a href="#">5PF-C-450-S</a>	5PF-C	cube	450 - 700 nm	$10^4 : 1$	> 95 %	4 mm	Ø 8 mm	-
<a href="#">5PF-C-750-S</a>	5PF-C	cube	750 - 1100 nm	$10^4 : 1$	> 95 %	4 mm	Ø 8 mm	-
<a href="#">5PF-C-1100-S</a>	5PF-C	cube	1100 - 1700 nm	$10^4 : 1$	> 98 %	4 mm	Ø 8 mm	-
<a href="#">5PF-C-400-L</a>	5PF-C	cube	390 - 480 nm	$10^4 : 1$	> 95 %	4 mm	Ø 8 mm	Ø 8 mm
<a href="#">5PF-C-450-L</a>	5PF-C	cube	450 - 700 nm	$10^4 : 1$	> 95 %	4 mm	Ø 8 mm	Ø 8 mm
<a href="#">5PF-C-750-L</a>	5PF-C	cube	750 - 1100 nm	$10^4 : 1$	> 95 %	4 mm	Ø 8 mm	Ø 8 mm
<a href="#">5PF-C-1100-L</a>	5PF-C	cube	1100 - 1700 nm	$10^4 : 1$	> 98 %	4 mm	Ø 8 mm	Ø 8 mm

## ACCESSORIES

### POLARIZATION ANALYZER SK010PA

Measurement tool for coupling into polarization-maintaining fiber cables

This is a printout of the page

<https://sukhamburg.com/products/fiberoptics/fibercoupler/accessories/attachmentoptics/pf/5.html> from 5/8/2024

## CONTACT

**For more information please contact:**

**Schäfter + Kirchhoff GmbH**

**Kieler Str. 212**

**22525 Hamburg**

**Germany**

**Tel: +49 40 85 39 97-0**

**Fax: +49 40 85 39 97-79**

**[info@sukhamburg.de](mailto:info@sukhamburg.de)**

**[www.sukhamburg.com](http://www.sukhamburg.com)**

## LEGAL NOTICE

**Copyright 2020 Schäfter+Kirchhoff GmbH. All rights reserved.**

Text, image, graphic, sound, video and animation files and their arrangement on Schäfter+Kirchhoff GmbH webpages are protected by copyright and other protective laws. The content may not be copied for commercial use or reproduced, modified or used on other websites. [\[more\]](#)